



CFC 6 TRI

Technical specifications. Compression F connector CFC 6 TRI

		CFC 6 TRI
Code		0703037
Description		Compression F connector for coaxial cable K 3xx series
Frequency Range		0,3 - 3000 MHz
Impedance		75 Ω
Amps Rating		5 A
Shielding Effectiveness (CoMet)		> 115 dB @ 1GHz > 110 dB @ 1000-3000 MHz
Transfer Impedance		< 0.12 m Ω /m @ 30MHz
Return Loss	0,3 - 500 MHz	- 41.8 dB
	500 - 860 MHz	- 38.8 dB
	860 - 1000 MHz	- 35.5 dB
	1000 - 1750 MHz	- 30.1 dB
	1750 - 2150 MHz	- 26.5 dB
	2150 - 3000 MHz	- 25.0 dB
Insertion Loss Max	0,3 - 500 MHz	<0,01 dB
	500 - 860 MHz	<0,01 dB
	860 - 1000 MHz	<0,01 dB
	1000 - 1750 MHz	<0,01 dB
	1750 - 2150 MHz	<0,03 dB
	2150 - 3000 MHz	<0,05 dB
Temperatura	Installing	- 5°C a + 50° C
	Operating	- 40°C a + 100° C
	Storing	- 40°C a + 100° C
Max. Tensile Strength		250 N
O-ring		EPDM color black
Inner Conductor: Resistance max.@1 A DC		Cable dat
Base Material	Body parts	Brass CuZn 39Pb3
	Inner Conductor	Brass CuZn 39Pb3
Plating	Body parts	Nitin
	Inner Conductor	Nitin
EAN 13 code		8436545306505
Packing quantity		100 / 2500