



Technical Features eXtreme HD Compact

Sleep Timer	TV-Radio	HDMI output
FTA Free channels	Electronic Program Guide (EPG)	Unicable1 & Unicable 2
Upgrade by USB	1 Scart	Image player
OSD multi-language	DiSEqC 1.0, 1.1, 1.2 - GoToX	Music player
Teletext	3500 channels	Video player

Logistic and commercial information

Measures: 145 x 100 x 32 mm	Code: 0720301	Packaging: 10 pcs
Weight: 0.28 Kg	EAN Code: 8436545306772	



Unicable



FULL HD



Ethernet



HDMI



Scart



ECO



USB
Update



Media
Player



Parent
Control



WiFi
Ready



Internet
Radio



USB W
Stick

High Definition Digital Satellite Receiver eXtreme HD Compact

VIDEO	
Decoding	MPEG-2 SD&HD, MPEG-4 H.264/AVC SD&HD
Bit rate	Max.20 Mbps
Aspect ratio	4:3PS, 4:3LB, 16:9, Auto
Active pixel (Scart, RCA)	AUTO, 720 x 576 @25fps, 720 x 480 @30fps
Active pixel (HDMI)	AUTO, TV, 480I, 480P, 576I, 576P, 720P_50, 720P_60, 1080I_25, 1080I_30, 1080P_50, 1080P_60, 1080P_25, 1080P_30 or 1080P_24
Output connector	HDMI / Scart
AUDIO	
Decoding	MPEG-2/MPEG-1 layer I, II & III, AC3
Mode	Mono, Dual, Stereo, Joint stereo
Bit rate	Max 384Kbps
Output connector	HDMI / Scart
DEMODULATOR	
Demodulation	QPSK, 8PSK
Multiplexing	SCPC/MCPC
Outer code	RS (204, 188, 8)
Inner code	ALL DVB rates
Energy dispersion	DVB-S & DVB-S2 recommendation
INPUT SIGNAL	
Frequency	950MHz ~ 2150MHz
Input level	-65dBm ~ -25dBm
Channel bandwidth	36MHz
Input socked	F-type connector
LNB CONTROL	
Power supply	13/18V (300mA max) with short circuit protection
Polarized control	Polarized control 13/18V polarization (V/H)
DiSEqC control	DiSEqC1.0, DiSEqC1.1, DiSEqC 1.2* and GoToX *
Unicable System	* This model does not allow to move motors Yes, Unicable and Unicable 2.
MISCELLANEOUS	
Ethernet Connector (LAN)	RJ 45
Ethernet Speed	10/100 Mbits
USB Connector	USB 2.0
Supply voltage and current	12VDC, 1.0A Max.
Stand-by power consumption	< 0,5 watt
(Low Power Consumption mode)	< 5 watts
External Power Supply	100-240V~50/60Hz 0.3A Max - 12VDC 1.0A 12W
P.S. Average active efficiency	83.72%
P.S. Efficiency at low load (10 %)	79.52%
P.S. No-load power consumption	0.08 W
Operation temperature	+5° to +40° C
Dimension (W x D x H)	145x100x32 mm
Weight	0.28 Kg

