


Reel K 290 WD GOLD



K 290 WD GOLD

Technical specifications. 6,8 mm coaxial cable. K 290 WD GOLD

CPR Dca



	K 290 WD GOLD		K 290 WD3 GOLD
Code	0703629		0703630
Inner conductor (mm) Ø	1,13 Cu		1,13 Cu
Dielectric (mm) Ø	4,6 PE - Physical foam		4,6 PE - Physical foam
Foil material	Al / Pet / Al (external layer copper colored)		Al / Pet / Al (external layer copper colored)
Braiding material	CCA copper colored		CCA copper colored
Number of wires (braiding)	128		128
Braiding composition	16 x 8 x 0,12 mm		16 x 8 x 0,12 mm
Outer jacket (mm) Ø	6,8 LSZH white		6,8 LSZH white
Screening factor (30 - 900 MHz)	> 90 dB		> 90 dB
Nominal attenuation (dB / 100 m)	47 MHz	3,7	3,7
	175 MHz	6,7	6,7
	470 MHz	11,2	11,2
	862 MHz	16,2	16,2
	950 MHz	17,5	17,5
	1350 MHz	21,8	21,8
	1750 MHz	25,0	25,0
	2150 MHz	28,2	28,2
Lenght	100 m		3 00 m
Impedance	75 Ω		75 Ω
Net weight	-		-
Reaction to fire	Dca-s1, d1, a1		Dca-s1, d1, a1
Declaration of Performance (DoP)	DoP- 0703629		DoP- 0703630
Presentation	100 m reel cardboard		300 m wooden cardboard
Packaging quantity	1 / 4		1 / 4

