



Keystone jack

Category 6 & 6A shielded



KJK-6-F-SI

KJR-6-F-SI

KJR-6A-F-SI

Technical specifications. Keystone jack Cat. 6 & 6A shielded

	KJK-6-F-SI	KJR-6-F-SI	KJR-6A-F-SI
Code	2220296	2220297	2220205
Description	Keystone jack 90° cat. 6, shielded, RJ45/u, silver	Keystone jack 180° cat. 6, shielded, RJ45/u, silver	Keystone jack 180° cat. 6A, shielded, RJ45/u, silver
Connector type	RJ45	RJ45	RJ45
Category	6	6	6A
Shielding	Yes	Yes	Yes
Anchoring system	Upper and lower flanges	Upper and lower flanges	Upper and lower flanges
Wiring diagram	T568A, T568B compatible	T568A, T568B compatible	T568A, T568B compatible
Material	Plastic, PC UL94V-0	Plastic, PC UL94V-0	Plastic, PC UL94V-0
Wire diameter	AWG 23-26	AWG 23-26	AWG 23-26
Color	Silver	Silver	Silver
Dimensions	46,6 x 21,2 x 19,5 mm	32,5 x 17,1 x 21,7 mm	32,55 x 17,1 x 19,3 mm
Standardisation	IEC 60603-7 Electrical Characteristics of the Telecommunication Outlets. ISO/IEC 11801, 2n edition EN 50173-1	IEC 60603-7 Electrical Characteristics of the Telecommunication Outlets. ISO/IEC 11801, 2n edition EN 50173-1	IEC 60603-7 Electrical Characteristics of the Telecommunication Outlets. ISO/IEC 11801, 2n edition EN 50173-1
EAN Code	8436049495613	8436049495620	8436049497754
Packaging quantity	1 / 10 / 100	1 / 10 / 100	1 / 10 / 100