





### Spécifications techniques. Filtres emboîtables série Lte Zn




|                               | Lte 5760 Zn                                                    | Lte 5770 Zn                                                      | Lte 5780 Zn                                                  | Lte 5790 Zn                                                  |
|-------------------------------|----------------------------------------------------------------|------------------------------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------------|
| <b>Code</b>                   | 0520316-01                                                     | 0520317-01                                                       | 0520318-01                                                   | 0520319-01                                                   |
| <b>Bande de passage</b>       | 5 – 766 MHz                                                    | 5 – 774 MHz                                                      | 5 – 782 MHz                                                  | 5 – 790 MHz                                                  |
| <b>Canal de coupure</b>       | C57                                                            | C58                                                              | C59                                                          | C60                                                          |
| <b>Pertes d'insertion</b>     | 5-700 MHz ≤ 1 dB<br>700-766 MHz ≤ 4 dB<br>790-1000 MHz ≥ 55 dB | 5-708 MHz: ≤ 1 dB<br>708-774 MHz: ≤ 4 dB<br>798-1000 MHz ≥ 55 dB | 5-716 MHz ≤ 1dB<br>716-782 MHz ≤ 4dB<br>806-1000 MHz ≥ 55 dB | 5-724 MHz ≤ 1dB<br>724-790 MHz ≤ 4dB<br>814-1000 MHz ≥ 55 dB |
| <b>Pertes de retour</b>       | 5-766 MHz ≥ 12 dB                                              | 5-774 MHz ≥ 12 dB                                                | 5-782 MHz ≥ 12 dB                                            | 5-790 MHz ≥ 12 dB                                            |
| <b>Passage de courant</b>     | Oui                                                            | Oui                                                              | Oui                                                          | Oui                                                          |
| <b>Dimensions (mm)</b>        | 89 x Ø 18,5                                                    | 89 x Ø 18,5                                                      | 89 x Ø 18,5                                                  | 89 x Ø 18,5                                                  |
| <b>Matériau</b>               | Zinc                                                           | Zinc                                                             | Zinc                                                         | Zinc                                                         |
| <b>Quantité par emballage</b> | 1 100 200                                                      | 1 100 200                                                        | 1 100 200                                                    | 1 100 200                                                    |




Lte 5760 Zn



Lte 5770 Zn



Lte 5780 Zn



Lte 5790 Zn

Graphiques de pertes d'insertion

