



Technical Features MAX S93+

Sleep Timer	Teletext	DiSEqC 1.1
Free channels FTA	Games	LPC: Low Power Consumption <0,5 Watt
Multi-language OSD	1 Scart	4000 channels
Electronic Program Guide (EPG)	TV-Radio	3 x RCA AV

Commercial and logistic information

Measures: 210 x 133 x 44 mm	Code: 0720058
Weight: 0.7 kg	Packaging: 5 pcs

MAX S93+

1 scart

Low Power Consumption <0,5 Watt

Free channels FTA

3X RCA AV

1
SCART

LPC

FTA

3X
RCA AV

BCN Distribuciones, S.A.U.

Corrals Nous, 77
Polígono Industrial Can Roqueta
08202 SABADELL (Barcelona)
Tel. +34 93 729 27 00 / Fax +34 93 729 30 73
info@ftemaximal.com



www.ftemaximal.com

Digital Satellite Receiver MAX S93+

VIDEO	
Decoding Bit rate Output Active pixel Output connector	MPEG-2 & MPEG-1 compatible Max 15Mbps PAL/NTSC 720x480 @ 30fps; 720x576 @25fps Scart, RCA
AUDIO	
Decoding Mode Bit rate Output connector	MPEG-2/MPEG-1 layer I & II Mono, Dual, Stereo, Joint stereo Max 384Kbps Scart, RCA
DEMODULATOR	
Demodulation Symbol rate Outer code Inner code Energy dispersion	QPSK SCPC/MCPC RS (204, 188, 8) ALL DVB rates DVB-S recommendation
INPUT SIGNAL	
Frequency Input level Channel bandwidth Input socked	950MHz ~ 2150MHz -65dBm ~ -25dBm 36MHz F-type connector
LNB CONTROL	
Power supply Polarized control DiSEqC control	13/18V (300mA max) with short circuit protection 13/18V polarization (vertical/horizontal) DiSEqC1.0, DiSEqC1.1 * This receiver does not allow moving DiSEqC motors
MISCELLANEOUS	
Supply voltage Power consumption Stand-by power consumption Operation temperature Dimension Weight	230VAC 50 Hz Typ. <5 watts / Max. 15 watts < 0.5 watts +5°C to +40°C 210 x 133 x 44 mm 0.7 Kg

