



MSR A 0508 SA



MSR A 0512 SA



MSR A 0516 SA



MSR A 0524 SA



MSR A 0532 SA

Spécifications techniques Commutateurs Série MSR

		MSR A-0508 SA	MSR A-0512 SA	MSR A-0516 SA	MSR A-0524 SA	MSR A-0532 SA
Code		0930180	0930182	0930184	0930186	0930188
Nombre d'entrées		4 SAT, 1 TER	4 SAT, 1 TER	4 SAT, 1 TER	4 SAT, 1 TER	4 SAT, 1 TER
Nombre de sorties		8	12	16	24	32
Connecteurs (F-con)		femelle	femelle	femelle	femelle	femelle
Marge de fréquences (MHz)	SAT	950-2200	950-2200	950-2200	950-2200	950-2200
	TER	47-862	47-862	47-862	47-862	47-862
Gain	SAT	5 ±1.5 dB	5 ±1.5 dB	5 ±1.5 dB	2 ±1.5 dB	2 ±1.5 dB
	TER	7 ±1.5 dB	7 ±1.5 dB	7 ±1.5 dB	7 ±1.5 dB	7 ±1.5 dB
Isolation	TER a SAT	≥ 30 dB	≥ 30 dB	≥ 30 dB	≥ 30 dB	≥ 30 dB
	SAT a TER	≥ 28 dB	≥ 28 dB	≥ 28 dB	≥ 28 dB	≥ 28 dB
Isolation entre les polarisations V/H		≥ 25 dB	≥ 25 dB	≥ 25 dB	≥ 25 dB	≥ 25 dB
Isolation	Sortie - Sortie TER	≥ 28 dB	≥ 28 dB	≥ 28 dB	≥ 28 dB	≥ 28 dB
	Sortie - Sortie SAT	≥ 35 dB	≥ 35 dB	≥ 35 dB	≥ 35 dB	≥ 35 dB
Pertes de retour	Entrées SAT	≥ 11 dB	≥ 11 dB	≥ 11 dB	≥ 10 dB	≥ 10 dB
	Sorties SAT	≥ 9 dB	≥ 9 dB	≥ 9 dB	≥ 8 dB	≥ 8 dB
	Entrées TER	≥ 11 dB	≥ 11 dB	≥ 11 dB	≥ 10 dB	≥ 10 dB
	Sorties TER	≥ 9 dB	≥ 9 dB	≥ 9 dB	≥ 8 dB	≥ 8 dB
Niveau de Sortie	SAT (IMD₃ - 35 dB)	100 dBμV	100 dBμV	100 dBμV	100 dBμV	100 dBμV
	TER (IMD₃ - 60 dB)	85 dBμV	85 dBμV	85 dBμV	85 dBμV	85 dBμV
Impédance Entrée / Sortie		75 Ohm	75 Ohm	75 Ohm	75 Ohm	75 Ohm
Commutation (VDC)		13V/18V / 13V/22 kHz / 18V/22 kHz				
Alimentation maximale LNB		13 VDC: 400 mA / 18 VDC: 1000 mA				
Alimentation VAC		~230V ± 15%, 50/60Hz, 3W				
Température de fonctionnement		- 10°C / 50°C				
Dimensions (L x H x P)		248x129x64 mm	288x129x64 mm	328x129x64 mm	408x129x64 mm	488x129x64 mm