

OLS 5x series

5 IN stand-alone passive multiswitches



OLS 56



OLS 58

Technical specifications. 5 IN stand-alone passive multiswitches OLS 5x series

		OLS 56	OLS 58	OLS 512	OLS 516
Code		0930070	0930072	0930074	0930076
Inputs TER / SAT		1 / 4	1 / 4	1 / 4	1 / 4
Tap outputs		6	8	12	16
Terrestrial	Frequencies (MHz)	5 - 862	5 - 862	5 - 862	5 - 862
	Losses (dB)	20 ± 2	21 ± 2	23 ± 2	24 ± 2
Satellite	Frequencies (MHz)	950 - 2400	950 - 2400	950 - 2400	950 - 2400
	Losses (dB)	0 ± 2	0 ± 2	0 ± 2	0 ± 2
	Isolation H / V (dB)	>20	>20	>20	>20
	Isolation SAT / SAT (dB)	>20	>20	>20	>20
	Max. Output level (dBuV)	105	105	95	95
Feeding, consumption		180 - 265 VAC, 47 - 63 Hz, 18 W			
22 KHz tone generator		No	No	No	No
LNC Max. consumption 18 V		500 mA	500 mA	500 mA	500 mA
Dimensions (mm)	(W x H x D)	305 x 115 x 80	305 x 115 x 80	400 x 115 x 80	400 x 115 x 80
Weight (gr)		650	680	870	1120
Packing quantity		1 / 5	1 / 5	1 / 5	1 / 5