



OLY 912



OLY 916

Technical specifications. 9 IN/OUT cascade multiswitches OLY 9x series

		OLY 98	OLY 912	OLY 916
Code		0930114	0930116	0930118
Nr of TER / SAT inputs		1 / 8	1 / 8	1 / 8
Nr of TER / SAT Outputs		1 / 8	1 / 8	1 / 8
Nr of TAP outputs		8	12	16
Terrestrial (passive)	Frequencies (MHz)	5 - 862	5 - 862	5 - 862
	TAP losses (dB)	23 ± 2	24 ± 2	25 ± 2
	Pass losses (dB)	5	6	7
	Isolation SAT / TER (dB)	>40	>40	>40
	Isolation REC / REC (dB)	>25	>25	>25
Satellite	Frequencies (MHz)	950 - 2400	950 - 2400	950 - 2400
	TAP losses (dB)	6 ± 2	6 ± 2	6 ± 2
	Pass losses (dB)	2 - 4	2 - 6	2 - 6
	Isolation H / V (dB)	>25	>25	>25
	Isolation SAT / SAT (dB)	>40	>40	>40
	Max. Output level (35dB IMR3) (dBuV)	102	102	102
Consumption from receiver	13 / 18 VDC	50 / 70 mA	50 / 70 mA	50 / 70 mA
Dimensions (mm)	(W x H x D)	280 x 110 x 80	280 x 190 x 80	280 x 190 x 80
Weight (gr)		860	1380	1390
Packing quantity		1	1	1