



OR series



Perfect contact

between the disc and the headend, which confers big robustness and wind resistance.



Solid headend

made of galvanized steel in an only piece. Abundant reinforcement **strips** and distance **limit** inserted.



Squared holes and special **anti-turn** screws.



Special nuts that allow using only one key of 13 mm for the whole antenna



Aluminium arm

with water-spills and leadthrough cable. **Anti-corrosion** guarantee.



And for the most **demanding ones**: LNC fixation in Zamack or lateral rod.

Technical specifications. Steel offset dishes OR series

		OR 58 SB	OR 58 SB-4	OR 58 SB-24	OR 80 SB	OR 80 SB-4	OR 80 SB-24
Code		0785811	0785811-4	0785811-24	0788011	0788011-4	0788011-24
Description		60 cm steel offset dish in beige colour			80 cm steel offset dish in beige colour		
Dimensions Vertical x Horizontal		580 x 510 mm			800 x 740 mm		
Reflector type		Offset			Offset		
Reflector material		Galvanized steel			Galvanized steel		
Support material		Galvanized steel			Galvanized steel		
Support arm material		Aluminum			Aluminum		
Paint		Epoxi - Poliester			Epoxi - Poliester		
Colour		RAL 7035 (Beige)			RAL 7035 (Beige)		
Frequency range		10,7 - 12,75 GHz			10,7 - 12,75 GHz		
Gain	10,7 - 11,7 GHz	35,0 dB			37,2 dB		
	11,7 - 12,75 GHz	35,5 dB			37,7 dB		
Azimut adjustment		0 - 360°			0 - 360°		
Elevation adjustment		10 - 60°			10 - 60°		
Operational wind resistance	130 Km/h	350 N			550 N		
	150 Km/h	450 N			750 N		
Maximum support diameter		60 mm			60 mm		
Weight		2,5 Kg			4.4 Kg		
Recommended supports		PG 32 (ref. 9003070) PG 40 (ref. 9003071) P 40 (ref. 9003048) P 40 L (ref. 9003048-L)			PG 40 (ref. 9003071) P 40 (ref. 9003048) P 40 L (ref. 9003048-L)		
Presentation		Box 1pc	Box 4pcs	Box 24pcs	Box 1pc	Box 4pcs	Box 24pcs