




RJ45-5e-U



RJ45-6-U



RJ45-6-F



RJ45-6-F-Eco

Technical specifications. RJ45 connectors


	RJ45-5e-U	RJ45-6-U	RJ45-6-F	RJ45-6-F-Eco
Code	2220208	2220207	2220209	2220203
Description	RJ45 connector Cat. 5e UTP	RJ45 connector Cat. 6 UTP	RJ45 connector Cat. 6 FTP with hook	RJ45 connector Cat. 6 FTP without hook
Connector type	RJ45 male	RJ45 male	RJ45 male	RJ45 male
Category	5e	6	6	6
Shielding	No	No	Yes	Yes
Mounting system	Internal guide	External guide	External guide	External guide
Supported conductors	AWG 24-26	AWG 23-26	AWG 23-24	AWG 23
Max. diameter conductor with cover	-	1,05 mm	1,35 mm	1,1 mm
Material	Plastic, PC UL94V-0 or UL94V-2			
Colour	Transparent	Transparent	Transparent and silver shielding	
External dimensions (mm)	22 x 12 x 11			
Standardization	ISO/IEC 11801, 2nd edition EN 50173-1			
Packing quantity	10 / 1000			

RJ45 Cat.6 FTP connectors

INSERTION GUIDES of CONDUCTORS with COVER




RJ45-6-F guide




RJ45-6-F-Eco guide

REAR INPUT, where net cable is inserted through



RJ45-6-F



RJ45-6-F-Eco

The RJ45-6-F model allows the entrance of thicker cables than the RJ45-6-F-Eco model, both as the pairs thickness and the outer cover thickness.