

SEM 17x series

17 IN stand-alone active multiswitches



SEM 178



SEM 1712



SEM 1724

Technical specifications. 17 IN stand-alone active multiswitches SEM 17x series

		SEM 178	SEM 1712	SEM 1724
Code		0930034	0930036	0930040
Inputs TER / SAT		1 / 16	1 / 16	1 / 16
Tap outputs		8	12	24
Terrestrial	Frequencies (MHz)	80 - 862	80 - 862	80 - 862
	Losses (dB)	0 ± 2	0 ± 2	0 ± 2
	Max. Output level (dBuV)	95	93	90
	Regulation (dB)	20	20	20
Return channel	Frequencies (MHz)	5 -65	5 -65	5 -65
	Losses (dB)	20 ± 2	23 ± 2	28 ± 2
Satellite	Frequencies (MHz)	950 - 2400	950 - 2400	950 - 2400
	Losses (dB)	0 ± 2	0 ± 2	0 ± 2
	Max. Output level (dBuV)	105	105	105
	Regulation (dB)	-	6	6
	Isolation SAT / SAT (dB)	>25	>25	>25
	Max. Output level (dBuV)	>40	>40	>40
Feeding		94-265 VAC, 47-63 Hz	94-265 VAC, 47-63 Hz	94-265 VAC, 47-63 Hz
22 KHz tone generator		Yes	Yes	Yes
LNC Max. consumption 12 / 18 V		600 / 1300 mA	600 / 1300 mA	600 / 1300 mA
Dimensions (mm) (W x H x D)		540 x 110 x 80	540 x 190 x 80	540 x 350 x 80
Weight (gr)		1562	2330	3660
Packing quantity		1	1	1