

Serie SEM 9x

Multiconmutadores estrella 8xSAT + Terrestre activo



SEM 96



SEM 912



SEM 932

Especificaciones técnicas. Multiconmutadores estrella 8xSAT + Terrestre activo SEM 9x

		SEM 94	SEM 96	SEM 98	SEM 912	SEM 924	SEM 932
Código		0930021	0930022	0930024	0930026	0930030	0930032
Entradas TER / SAT		1 / 8	1 / 8	1 / 8	1 / 8	1 / 8	1 / 8
Salidas derivación		4	6	8	12	24	32
Terrestre	Frecuencias (MHz)	80 - 862	80 - 862	80 - 862	80 - 862	80 - 862	80 - 862
	Pérdidas (dB)	0 ± 2	0 ± 2	0 ± 2	0 ± 2	0 ± 2	0 ± 2
	Máx. Nivel salida (dBuV)	95	95	95	93	90	90
	Regulación (dB)	-	-	-	-	20	20
Canal de retorno	Frecuencias (MHz)	5 - 65	5 - 65	5 - 65	5 - 65	5 - 65	5 - 65
	Pérdidas (dB)	19 ± 2	20 ± 2	20 ± 2	23 ± 2	28 ± 2	30 ± 2
Satélite	Frecuencias (MHz)	950 - 2400	950 - 2400	950 - 2400	950 - 2400	950 - 2400	950 - 2400
	Pérdidas (dB)	0 ± 2	0 ± 2	0 ± 2	0 ± 2	0 ± 2	0 ± 2
	Aislamiento H / V (dB)	>25	>25	>25	>25	>25	>25
	Aislamiento SAT/SAT (dB)	>20	>20	>20	>20	>20	>20
	Máx. Nivel salida (dBuV)	105	105	105	105	105	105
Alimentación desde el receptor 13 / 18 V		70 mA	70 mA	70 mA	70 mA	70 mA	70 mA
Alimentación, consumo		180 - 265 VAC, 47 - 63 Hz, 26 W					
Generador tono 22 KHz		Sí	Sí	Sí	Sí	Sí	Sí
Consumo máx. LNC 12/18V		500 / 700 mA	500 / 700 mA	500 / 700 mA	500 / 700 mA	500 / 700 mA	500 / 700 mA
Dimensiones (mm)	(An. x Al. x P)	400 x 100 x 80	400 x 100 x 80	400 x 100 x 80	400 x 190 x 80	400 x 350 x 80	400 x 350 x 80
Peso (gr)		1060	1070	1080	1600	1650	1700
Cantidad por embalaje		1 / 5	1 / 5	1 / 5	1	1	1