

Tangle and Twist-Free Packaging Technology



**Standard
coils**



**REELEX®
coils**




**Spools &
reels**

Sometimes known as a “pull box” package **REELEX®** is a **patented method** of winding cable or any cord-like product in such a way as to result in a reel-less, self supporting coil. This unique coil dispenses from the inside-out without twists, tangles, snags or overruns.

N 600 WE R



Code	2220654
Description	LAN Cable U/UTP Cat. 6 Cu LSZH 305m (1000ft)
Category	6 - U/UTP
Conductor material	Cu (copper)
Conductor diameter	0,51 mm
Pair cover material	PE
Ripcord	Si
Jacket diameter	5.8 ± 0.3 mm
Color cubierta exterior	White
Lenght	305 m (1000 ft)
Weight	10,9 Kg
Standarization	ISO/IEC 11801, EN 50173, EN 50288, EIA/TIA 568C.2, EN 50575:2014+A1:2016
Reaction to fire	CPR-Eca



30%

**Faster
installations**

35%

**Less waste volume
than spools**

0

**Twists, tangles,
rotation or tension**

Preferred by installers

Save time and labor

No need for stands or brakes.
Pull product up to **30% faster**
than reels or spools.

Improve your work

Product pulls with no tension,
no twists, no tangles, no overruns,
no spills, no splinters,
no brakes, no tension control.
No hassles. Just pull.

Less waste

REELEX packaging is easy to
recycle, easy to break down and
produces **less material waste**
than reels or spools.



How are REELEX coils made?

REELEX coils require **patented REELEX machines.**

For over 40 years, we have been designing and manufacturing unique
REELEX coiling machines and supporting **ancillary equipment.**

For more information visit **www.reelex.com**

BCN Distribuciones, S.A.U.

Agustí Pi i Sunyer, 15
08192 Sant Quirze del Vallès (Barcelona)
Tel. +34 93 729 27 00 / Fax +34 93 729 30 73
info@fitemaximal.com



www.fitemaximal.com