

# MAX T250 HD

## Digital Terrestrial Receiver



MAX T250 HD



Accessories and remote MAX T250 HD

**Practical and compact receiver**, it hides neatly behind the TV, connects to an HDMI port and is controlled by infrared with the external sensor supplied, for a quality enjoyment of the full range of free-to-air SD and HD programmes. Equipped with a convenient 2-in-1 universal remote control, the **MAX T250 HD allows you to play photos, videos and audio thanks to the media player function**. It has the LCN function for logical and automatic ordering. It is capable of storing up to 5000

### Main features:

- Up to 5,000 TV and Radio channels
- Automatic Channel Search & Sorting (LCN)
- EPG function, 24-hour electronic program guide
- Multimedia playback (photos, audio, video)
- Multi-lingual menu, teletext option and subtitles
- Supports the DVB-T2 HEVC H.265 10-bit core standard
- Conexiones RF IN, HDMI, IR, USB, CC
- Compact size, quick and easy installation
- Infrared sensor supplied
- Software update via USB 2.0
- Included accessories: 30 cm HDMI cable; 2-in-1 remote control; 2 x AAA batteries; IR receiver cable; 5V/1.5A power supply; user manual

|                                         |                                                                                                                                                        |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Code                                    | IMA08P0710042                                                                                                                                          |
| Supported Programs                      | SD/HD FTA                                                                                                                                              |
| Supported Standards                     | DVB-T, DVB-T2                                                                                                                                          |
| Input modulation                        | 64QAM, 256QAM                                                                                                                                          |
| Supported Video Codecs                  | MPEG-2, MPEG-4/H.264 AVC, HEVC/H.265 Main 10 bit                                                                                                       |
| Appearance format                       | 4:3, 16:9                                                                                                                                              |
| HDMI video resolution max.              | 1080p@60Hz                                                                                                                                             |
| Supported audio codecs                  | PCM, MPEG-1, SPDIF, Dolby Digital, Dolby Digital+                                                                                                      |
| Number of storable channels             | 5.000                                                                                                                                                  |
| OSD menu languages                      | IT, EN, FR, ES, PT, DE, NL                                                                                                                             |
| Primera guía de instalación             | Yes                                                                                                                                                    |
| First installation guide                | Yes                                                                                                                                                    |
| Radio mode                              | Yes                                                                                                                                                    |
| Signal quality/level indicator          | Yes                                                                                                                                                    |
| Audio/video output                      | 1 HDMI                                                                                                                                                 |
| Digital audio output S/PDIF             | No                                                                                                                                                     |
| Input Frequency                         | 50 - 870 MHz                                                                                                                                           |
| Input level                             | 45 - 100 MHz                                                                                                                                           |
| Type of connections                     | RF IN: IEC female                                                                                                                                      |
| Update via OTA                          | Yes                                                                                                                                                    |
| Remote Power Supply - VCC               | Active antennas: VDC: 5                                                                                                                                |
| Supply Voltage - VCA/Hz                 | 100 - 240 - 50/60 VAC/Hz                                                                                                                               |
| Max consumption                         | Max. 7,5 W                                                                                                                                             |
| Operating temperature                   | -5 °C - +45 °C                                                                                                                                         |
| Dimensions (An. x Al. x Pr.)            | 105 x 17 x 40 mm                                                                                                                                       |
| Dimensions gift box                     | 10 x 18,5 x 5,5 cm                                                                                                                                     |
| Gross and net weight gift box           | 272 g / 207 g                                                                                                                                          |
| Dimensions and GW and NW for master box | 39 x 29,5 x 22,5 cm<br>G.W: 6,0 kg N.W: 5,5 kg                                                                                                         |
| Qty/master box                          | 20 pc                                                                                                                                                  |
| Box contents                            | - Receiver<br>- 2 in 1 remote control<br>- 2 AAA batteries<br>- IR Receiver Cable<br>- 5V/1.5A Power Supply<br>- HDMI Male/Male Cable<br>- User manual |
| Standards Compliant                     | CE / ROHS                                                                                                                                              |
| Code EAN                                | 8055271136455                                                                                                                                          |
| HS CODE                                 | 8528719100                                                                                                                                             |